

## Safety Data Sheet (91/155/EEC)

ITW Dykem

Revision date: 11.10.2006 No.: 2,00

### RINZ OFF (WASHED-OUT) [Blue, Red, Green, Black]

00392-0008

---

## **1. Identification of the substance/preparation and company**

### **1.1 Commercial product name**

RINZ OFF (WASHED-OUT) [Blue, Red, Green, Black]

#### **Art.-No.:**

44105, 44106, 44108, 44109

91105, 91106, 91108, 91109

Colours: blue, red, green, black

#### **Use of the substance/preparation**

Industrial paint marker

### **1.2 Information manufacturer/supplier**

ITW Dykem

805 E. Old 56 Highway

Olathe, KS 66061

Telephone: 001 913 397 9889 Telefax: 001 913 397 8761

24 Hour Emergency Contact: 001 352 323 3500

---

## **2. Composition/information on ingredients**

### **Chemical characterization : ( preparation )**

Preparation in organic solvents

### **Hazardous components**

(Full text of each relevant R phrase can be found in heading 16)

EC No.	CAS No.	Components	Value	Symbols	R-phrases
204-626-7	123-42-2	4-hydroxy-4-methylpentan-2-one	25 - 35 %	Xi R36	
200-746-9	71-23-8	propan-1-ol	55 - 65 %	F, Xi	R11-41-67

---

## **3. Hazards identification**

### **Explication of special hazards for human health and environment**

Flammable.

Risk of serious damage to eyes.

Vapours may cause drowsiness and dizziness.

---

## **4. First aid measures**

### **General information**

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

### **After inhalation**

Move to fresh air in case of accidental inhalation of vapours.

Consult a physician.

If patient is not breathing, apply artificial respiration.

### **After contact with skin**

Rinse with plenty of water.

Consult a doctor if skin irritation persists.

## Safety Data Sheet (91/155/EEC)

ITW Dykem

Revision date: 11.10.2006 No.: 2,00

### **RINZ OFF (WASHED-OUT) [Blue, Red, Green, Black]**

00392-0008

---

#### **After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

#### **After ingestion**

Do not induce vomiting.  
Summon a doctor immediately..  
Never give anything by mouth to an unconscious person.

---

## **5. Fire-fighting measures**

### **Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray

### **Extinguishing media that must not be used for safety reasons**

Full water jet

### **Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases**

Fire may produce:

Carbon monoxide and carbon dioxide.

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

### **Special protective equipment for firefighters**

Wear self-contained breathing apparatus and protective suit.

### **Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

---

## **6. Accidental release measures**

### **Personal precautions**

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

### **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

### **Methods for cleaning up/taking up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

### **Additional information**

Clean contaminated surface thoroughly.

---

## Safety Data Sheet (91/155/EEC)

ITW Dykem

Revision date: 11.10.2006 No.: 2,00

### RINZ OFF (WASHED-OUT) [Blue, Red, Green, Black]

00392-0008

## 7. Handling and storage

### 7.1 Handling

#### Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

Use only in thoroughly ventilated areas.

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

### 7.2 Storage

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

#### Advice on storage compatibility

Incompatible with:

strong acids and strong bases

strong oxidizing agents, reducing agents

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Storageclass (VCI): 3 A

---

## 8. Exposure controls/personal protection

### 8.1 Exposure limit values

#### Exposure limits (EH40)

Components CAS No.	Exposure limit ml/m <sup>3</sup>	mg/m <sup>3</sup>	F/ml	Category	Origin
4-Hydroxy-4-methyl-pentan-2-one					
123-42-2	50	241		TWA (8 h)	OES
	75	362		STEL (15 min)	OES
Propan-1-ol					
71-23-8	200	500		TWA (8 h)	OES
	250	625		STEL (15 min)	OES

### 8.2 Exposure controls

#### Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Treat subsequently with skin cream.

Take off immediately all contaminated clothing.

Avoid contact with skin, eyes and clothing.



## Safety Data Sheet (91/155/EEC)

ITW Dykem

Revision date: 11.10.2006 No.: 2,00

### **RINZ OFF (WASHED-OUT) [Blue, Red, Green, Black]**

00392-0008

---

## **10. Stability and reactivity**

### **Conditions to avoid**

Vapours may form explosive mixture with air.

### **Materials to avoid**

strong acids and strong bases  
strong oxidizing agents, reducing agents

### **Hazardous decomposition products**

Carbon monoxide and carbon dioxide  
Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

### **Additional information**

No decomposition if stored and applied as directed.

---

## **11. Toxicological information**

### **Empirical data on effects on humans**

risk of strong eye injuries  
Vapours may cause drowsiness and dizziness.

### **Additional information**

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.  
Effects of breathing high concentrations of vapour may include headache, dizziness, weakness, unconsciousness  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

---

## **12. Ecological information**

### **Additional information**

Do not flush into surface water or sanitary sewer system.  
Slightly water hazardous.

---

## **13. Advice on disposal**

### **Dispose**

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

### **Waste disposal number of Waste from residues / unused product : 080111**

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other dangerous substances  
Classified as hazardous waste.

### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

---

**Safety Data Sheet (91/155/EEC)**

ITW Dykem

Revision date: 11.10.2006 No.: 2,00

**RINZ OFF (WASHED-OUT) [Blue, Red, Green, Black]**

00392-0008

---

**14. Transport information**

**14.1 Land transport (ADR/RID)**

ADR/RID: 3  
Hazard-no.: 30  
UN number: 1263  
Hazard label: 3  
ADR packaging group: III

**Description of the goods:**

PAINT

**Remarks**

"LQ 7: combination packaging: 5 l / 45 l; trays: 5 l / 20 l (20 kg total gross mass)"

**14.2 Inland waterways transport**

**14.3 Marine transport**

IMDG-Code: 3  
UN number: 1263  
EMS: F-E; S-E  
Packaging group: III  
Marine pollutant: No

**Description of the goods**

PAINT

Hazard label: 3

**Remarks**

Limited quantities (section 3.4): combination packaging: 5 l / 30 kg (total gross mass); trays: 5 l / 20 kg (total gross mass)

**14.4 Air transport**

ICAO/IATA-DGR: 3  
UN/ID number: 1263  
Hazard label: 3

IATA-packing instructions - passenger: 309  
IATA-max. quantity - passenger: 60 L  
IATA-packing instructions - Cargo: 310  
IATA-max. quantity - Cargo: 220 L

ICAO-packaging group: III

**Description of the goods**

PAINT

**14.5 Further Information**

---

**Safety Data Sheet (91/155/EEC)**

ITW Dykem

Revision date: 11.10.2006 No.: 2,00

**RINZ OFF (WASHED-OUT) [Blue, Red, Green, Black]**

00392-0008

---

**15. Regulatory information**

**15.1 Labelling**

**Labelling according to EC-guidelines**

As an article the product does not need to be labelled in accordance with EC-directives or respective national laws.

**15.2 National regulations**

Water contaminating class: 1 - slightly water contaminating  
1999/13/EC (VOC): < 95 %

---

**16. Other information**

**List of relevant R phrases**

- 11 Highly flammable.
- 36 Irritating to eyes.
- 41 Risk of serious damage to eyes.
- 67 Vapours may cause drowsiness and dizziness.

**Other data**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

---